



Toyo Seiki Seisaku-sho, Ltd. 5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

No. 107 Container Compression Tester Model T5-E



■ APPLICATION

The **Container Compression Tester** evaluates compression strength of large size containers used for packaging (such as corrugated boxes) etc.

■ SPECIFICATIONS

Model	T5-E
Load cell capacity	Max. 50kN
Load range	50kN(x1), 25kN(x2), 10kN(x5), 5kN(x10), 2.5kN(x20), 1kN(x50), 0.5kN(x100)
Compression plate dimensions	1200 x 1200mm
Compression plate stroke	1500mm
Cross-head speed range	■ 0.5, 1, 2, 3, 5, 10, 20, 25, 30, 50, 100mm/min. (11 steps) ■ In addition to above, one point of any speed is possible to set by 0.5mm/min. step within above range (Service Speed)
Cross-head return speed	Max. 100mm/min.
Cross-head speed accuracy	±1%
Safety device	■ Rod type limiter ■ Emergency stop switch
Power requirement	Three-phase, AC200V, 50Hz or 60Hz, 5.2kVA
Dimensions	W2080 x D1200 x H2840mm
Weight	Approx. 2450kg
Related standard	JIS Z 0212

Specifications are subject to change without notice.



TOYO SEIKI SEISAKU-SHO, LTD.

5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

Tel:+81-3-3916-8183 Fax:+81-3-3916-8173

www.toyoseiki.co.jp

20191204 MN