

Toyo Seiki Seisaku-sho, Ltd. 5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

No. 177 Standard Sheet Machine



Note: Metal rack is option

APPLICATION

In order to test physical properties of pulp, it is necessary to ascertain the affect that various controlling factors such as pulp material, various conditions for pulping, conditions for beating method, filler sizing agent, etc. have on the properties of paper prior to preparing test specimen. This machine is a hand-operated sheet machine used for estimating these values with a small amount of sample and is most widely used for this purpose.

SPECIFICATIONS

Sheet Forming Device

Model	D158-M	
Sheet forming area	Diameter Ø158mm	
Screen wire	106μm (Approx. 150 mesh)	
Couch roll weight	13kg	

Air Sheet Press, model E-1

Model	E-1	
Press system	Pneumatic	
Max pressure	410kPa	
Stroke	Max approx. 150mm	
Compressed air supply	0.4MPa	
Dimensions	W350 x D300 x H700mm	
Net weight	Approx. 50kg	

Sheet Drying Device, model D158-D

Model	D158-D
Power supply	Single-phase, AC100V, 50/60Hz, 0.05kVA

Set of D158-M + E-1 + D158-D

Model	D158-S	
Dimensions	Approx. W1300 x D600 x H1400mm (Including optional metal rack)	
Net weight	Approx. 120kg (Including optional metal rack)	

OPTION

Name	Model (Part No.)	Photo
Metal rack	DSK	

Specifications are subject to change without notice.



20200819 MN